

R5-CX RETAILER ASSEMBLY MANUAL

cervélo

cervélo

TABLE OF CONTENTS

Important Information	1
List of Tools & Supplies	2
R5-CX Parts List	3
R5-CX Frame Features	4
Small Parts	5
ST31 Stem	7
HB13 Handlebar	9
Frame & Component Preparation	11
Fork Preparation & Installation	13
Brake Hose Routing	15
Electric Wire Routing & Installation	17
Seatpost Assembly & Installation	19
Di2 Battery Installation	20
Aero Thru-Axle Installation	21
Tire/Rim Clearance	23
Intended Use of the R5-CX Bicycle	24
R5-CX Torque Specifications	25
R5-CX Frame Details	27
R5-CX Frame Geometry	28
Cervélo Customer Support	29

IMPORTANT INFORMATION

This manual is intended to guide official Cervélo retailers through the assembly and adjustment of the Cervélo R5-CX. This manual outlines the process and procedure associated with the installation of Cervélo components, as well as the routing of shifting and braking control lines only. Proprietary parts referenced in this manual are available only through Cervélo Cycles Inc.

Failure to use the specified parts and follow these assembly instructions, may result in loss of control while riding; and lead to serious injury. This manual is not intended to replace the assembly and service instruction provided by third-party component manufacturers, and assumes that the assembler is a trained, professional bicycle mechanic. See <https://www.probma.org/>





NOTE: Cervélo strongly recommends that all assembly and adjustment procedures be performed by an authorized Cervélo retailer. If you are a Cervélo R5-CX consumer/purchaser reading this manual we suggest that before attempting to undertake any of the procedures in this manual that you consult your authorized Cervélo retailer, or visit us at www.cervelo.com/support

LIST OF TOOLS & SUPPLIES

This manual outlines a number of procedures for making adjustments to the R5-CX bicycle. The following tools and parts listed are required for these adjustments. Cervélo strongly recommends that all assembly and adjustment procedures be performed by an authorized Cervélo retailer.

NOTE: All non-proprietary components such as those from Shimano or SRAM are available from your local distributor.

NOTE: This manual was developed to compliment the Cervélo General User Manual, and is intended as a supplement to the assembly and installation instructions supplied by the component manufacturers (provided with this bicycle).

Tools	Tools
	Bicycle workstand (types which secure bike by the seatpost, or pro-type stand with fork mount)
	Torque wrench(es) with 2.5Nm to 15Nm range and adaptors:
	Allen (Hex) head inserts: 2mm, 2.5mm, 3mm, 4mm, 5mm, 6mm, 8mm, 10mm
	Open ended wrenches: 7mm, 8mm, 10mm, 17mm
	Cable cutters
	Pliers
	Phillips-head screwdriver
	Slot-head screwdriver
	Pedal wrench
	Lockring tools for brake rotors and bottom bracket
	Hydraulic bleed kit
	Isopropyl alcohol
	Di2 wire tool – Shimano
	Good quality bicycle grease & carbon assembly compound
	Saw cutting guide (ParkTool SG-7.2 or equivalent)
	Hacksaw (with carbon and aluminum specific blades)


R5-CX PARTS LIST

Item Description	Cervélo Part No.
BB Blanking Plug	GR-BB-140
Rear Derailleur Hanger w/Fixing Nut	DRH-WMN112
Shimano Direct Mount RDH w/Fixing Nut	DRH-SDM
Threaded Fork Insert w/Fixing Screw	QRI-THD
SeatTube Blanking Plug(1x & Wireless)	GR-576
Brake Hose Guide	CBG-DBH
Front Derailleur Mount w/ Fixing Screws	FDM-590
Front Derailleur Mount Blanking Plate (1x)	FDM-CVR
Dropout Blanking Plug Wireless	GR-DRPOUT-CLOSED

Item Description	Cervélo Part No.
Dropout Electric Wire Guide	GR-DROPOUT-GUIDE
SP24 Seatpost w/ Head 0mm	SP-SP24-ZERO
SP24 Seatpost w/ Head 15mm	SP-SP24-15MM
SP18 Seatpost w/ Head 25mm	SP-SP18-25MM
Seatpost Battery Mount	MT-BINT-SP2
D-Shaped Seatpost Clamp & Secondary Seatpost Clamp Kit	SPC-256
Cervélo Front Aero Thru-Axle	QRA-AERO2-F
Cervélo Rear Aero Thru-Axle	QRA-AERO2-R
Cervélo Aero Thru-Axle Removable Handle	QRA-AERO2-HNDL
Chainstay Protector	PRO-CS-508


Item Description	Cervélo Part No.
Rubber Plug for ST32 Top Cap	PL-338
ST31/32 Top Cap	STC-305
ST32 Bearing Cap Kit (7mm & 22mm)	BC-ST32
ST31/32 HS Spacer Kit	SK-032
Split Ring 312	SR-312
D-Shaped Compression Plug	FKI-CL005-517A
ST31/32 Accessory Mount Assembly	MT-LM-F-004
Accessory Mount Kit- Rear	MT-LM-R-003

R5-CX FRAME FEATURES




SMALL PARTS


The R5-CX frame is engineered to provide seamless integration of electronic shifting systems, regardless of brand. In order to do so, you may require the parts shown below:




Seatpost
Battery Mount
MT-BINT-SP2



Accessory Mount
Kit (Rear)
MT-LM-R-003



ST31 Computer/Accessory
Mount Assembly
MT-LM-F-004



See pages 12 and 19 for mounting instructions.

ST31 STEM

Cervélo ST31 Stem
(Carbon)

80mm ST-C031-80

90mm ST-C031-90



100mm ST-C031-100

110mm ST-C031-110

120mm ST-C031-120



130mm ST-C031-130

ST32 Stem Top
Cap STC-305



To mount a cycling computer or accessory such as a light or camera, use Accessory Mount Kit-Front MT-LM-F-004 See page 10 for assembly instructions.

Tighten fork
steerer fixing
screws to 5Nm.




M5 x 16mm
ST31 stem
faceplate fixing
screw (Actual
size)


WARNING

Use only original Cervélo components & included hardware specified for handlebar, stem, and fork assembly. Failure to use the specified parts and to follow these instructions may result in a loss of control while riding and serious injury.

1. Coat the surfaces where the stem body and faceplate contact the handlebar clamping area (as shown right) with carbon assembly paste.
2. Center the handlebar against the stem body and secure it in place by mounting the faceplate and tightening all faceplate fixing screws finger-tight.
3. Tighten the faceplate fixing screws evenly following a star pattern until the upper and lower stem to faceplate gaps are even.
4. Perform final tightening in a star pattern using a torque wrench to 6Nm maximum.



Ensure upper
and lower
faceplate
gaps are
even.





Do not
flip ST31
stem for
additional
stack.

HB13 HANDLEBAR

⚠️ WARNING

Use only original Cervélo components & included hardware specified for handlebar, stem, and fork assembly. Failure to use the specified parts and to follow these instructions may result in a loss of control while riding and serious injury.



Cervélo HB13 Handlebar
38cm HB-HB13-38
40cm HB-HB13-40
42cm HB-HB13-42
44cm HB-HB13-44



FRAME & COMPONENT PREPARATION

⚠️ WARNING

Hold the frame using a secured seatpost only. Clamping the top tube can damage the frame and void your warranty.




⚠️ WARNING

If trimming of the seatpost is required, final length should allow for a minimum of 70mm of seatpost remaining in the frame, or the minimum insertion dimension indicated on the seatpost, whichever is greater. Failure to meet this requirement, may result in damage to the frame not covered by warranty policy, or serious injury to rider.

FRAME & COMPONENT PREPARATION

Install Front Derailleur Mount (FDM-590), and ensure fixing screws are torqued to 3Nm.




Lightly grease Rear Derailleur Hanger Fixing Nut and install either Rear Derailleur Hanger (DRH-WMN112) or Direct Mount Rear Derailleur Hanger (DRH-SDM) finger tight. Final tightening will be performed after rear wheel installation.




WARNING
Do not final tighten rear derailleur hanger assembly without rear wheel installed. Doing so may result in a misaligned derailleur and poor shifting.


For 1x systems replace with the Front Derailleur Mount Blanking Plate (FDM-CVR).



1. Lightly grease supplied M4 fixing screw. Install the Threaded Fork Insert (QRI-THD) and fixing screw, tightening only lightly.
2. Without wheel in place, install the axle and tighten until the flange meets the fork dropout face, but does not compress the fork blades.
3. Tighten the fixing screw to 3Nm.
4. Remove the axle and install wheel. Reinstall axle and tighten to 12-15Nm.
5. Remove axle and wheel, and re-torque the fixing screw to 3Nm.





Clean the chainstay using isopropyl alcohol. Install the Chainstay Protector (PRO-CS-508) by removing adhesive backing, and fixing the guard to the frame. The bottom rearward edge should be approximately 50mm forward from the back of the rear dropout.



To install Accessory Mount - Rear (MT-LM-R-003), replace the rear upper crossbar of the seatpost with the kit version. Tighten to maximum 8Nm. See also page 19.

To install ST31 Accessory Mount (MT-LM-F-004), angle mount into ST31 stem faceplate and torque to 2Nm.



For use without accessory, clip may be hidden, by reversing the crossbar.

FORK PREPARATION & INSTALLATION

1. Apply grease to the bearing pockets and install the upper and lower headset bearings into the frame.
2. Fit the fork provided with your frame into the head tube with the complete headset, required spacers, and the stem.
3. Apply the minimum pressure needed to ensure the assembly is fully seated. Mark the steerer tube at the top of the stem.
4. Remove fork and clearly mark the fork steerer tube at a point 4mm below the first mark. Take care to verify that this measurement is correct as this defines the cut line for the steerer tube.
5. To trim fork steerer, use only a saw suitable for cutting carbon, and a cutting guide.
6. Insert D-Shaped Compression Plug and tighten to hold in place. Do not apply final torque until after the stem is installed.
7. Place Lower Bearing over the fork steerer and insert into the frame from the bottom of the head tube.
8. Lightly coat the fork steerer at the stem clamping interface with carbon assembly compound. Install over the steerer in order: Upper Bearing, Split Ring, Bearing Top Cap, Stem Spacers, and Stem. Do not install the Stem Top Cap.
9. Tighten the Compression Plug to 8Nm using a torque wrench.
10. Install the Stem Top Cap and Preload Fixing Screw into the stem. Tighten the Preload bolt only enough to remove all play from the headset, and ensure the bearings rotate freely (typically 1 to 2 Nm)
11. Tighten the stem to fork fixing bolts to 5Nm maximum.

WARNING


Avoid breathing the dust created during cutting carbon composite materials.

WARNING



Improper cutting of the steerer tube could cause a failure that may result in severe injury or death.

WARNING

Do not exceed 52mm maximum total spacer height, including the Bearing Top Cap.




CAUTION
Do not exceed 5mm total spacers above the stem.




D-Shaped Compression Plug adds 1mm to height of cut fork

CAUTION
The component parts of the compression plug are side-specific. Re-assembling parts incorrectly may result in loss of preload in the system. Refer to the images shown for correct assembly.



WARNING
Do not torque Compression Plug past the recommended 8Nm maximum. If the Compression Plug requires tightening past 8Nm, please contact Cervélo Customer Service.



Two-piece Stem Spacers allow for installation or removal without re-cabling.


WARNING
Your Cervélo frame & fork have been designed to work together. Do not substitute a different size fork without first consulting Cervélo Customer Service to confirm compatibility with your frame.

BRAKE HOSE ROUTING

These routing illustrations are intended as a supplement to the manufacturer's installation instructions only. For both hydraulic and mechanical disc brakes, please refer to the component manufacturer's service center or website for further information.




Route rear
brake hose
from
chainstay
through
the down
tube and
up through
the
head
tube.




Route rear
brake hose
around drive
side of fork
inside head
tube.

It is recommended to include
20mm-25mm of additional brake
hose length to the amount required
for the final customer fit. Doing
so will permit sufficient length for
disassembly and service purposes.

1. Measure customer fit
2. Add additional 20-25mm of spacers
3. Cut and install brake hoses
4. Remove extra spacers
5. Complete assembly




Route hydraulic brake hose through the frame and fork with the Disc Hose Guide (CBG-DBH). Install and adjust calipers as per manufacturer's instructions.



Route brake hose
through Split
Ring, Bearing Top
Cap and out ST31
stem.

Split Ring
(SR-312)





ELECTRIC WIRE ROUTING & INSTALLATION


These routing illustrations are intended as a supplement to the manufacturer's installation instructions only. Please refer to the component manufacturer's service center or website for further information.

Brake


E-Wire (SD300)



With all wires inside, cap the Bottom Bracket Cable Port with the BB Blanking Plug (GR-BB-140).



Install the Rear Derailleur Wire Guide (GR-DRPOUT-GUIDE).



For wireless shifting systems install the Rear Derailleur Blanking Plug (GR-DRPOUT-CLOSED).


SEATPOST ASSEMBLY & INSTALLATION

1. Apply a light coat of carbon assembly compound to the upper face of the Seatpost, making sure to cover area around the adjustment slots.
2. Locate saddle rail between Crossbars and Saddle Clamp Base, and place on Seatpost.
3. With alignment washers installed, attach assembly to Seatpost, by tightening lightly greased fixing screws, alternating between the two sides each 1/2 turn. Once saddle is adjusted, tighten fixing screws to a maximum of 8Nm.




Torque fixing screws to 2.5Nm.

Replace rear upper clamp with Accessory Mount kit version. Tighten to maximum 8Nm.




DI2 BATTERY INSTALLATION


The battery for your Shimano Di2 system mounts inside the seat tube using the Seatpost Internal Battery Mount (MT-BINT-SP2). As this is an enclosed location, it is important to test the system prior to final installation.




AERO THRU-AXLE INSTALLATION



6mm Allen key /
torque wrench
or




Cervélo Aero
Thru-Axle with
Removable Handle
(QRA-AERO2-F,
QRA-AERO2-R &
QRA-AERO2-HNDL)





To secure wheels, install the greased axle, through the drop out and the wheel hub, aligning the threaded end of the axle with the threaded insert. Once aligned and engaged, thread the axle (clock-wise) into the threaded component of the insert until the axle is secured tightly.

WARNING

To ensure rider safety, it is critical to install the Cervélo Aero Thru-Axle correctly. Failure to do so may result in an accident with potential for serious injury to the rider.



Tighten rear axle
to 12-15Nm.




Perform final tightening on
Rear Derailleur Hanger Nut
using a 17mm wrench. Torque
to 12-15Nm. This action is
unique to initial assembly, and
should not require additional
adjustment.

WARNING
Adjust brakes as per manufacturer's
instructions.

TIRE/RIM CLEARANCE

Your Cervélo bicycle complies with the ISO 4210-2:4.10.2 standard for tire clearance. In order to comply with these safety standards and maintain your Limited Lifetime Warranty, a minimum of 4mm of clearance must remain between the tire and any frame element. Due to the growing complexity of tire and rim interfaces, Cervélo recommends identifying the available space before choosing a tire.



1. Measure the space between the chainstays at the bottom bracket junction.
2. Measure the space between the seatstays at the top of the tire.
3. Using the smallest of those two numbers, subtract 8mm (4mm per side) to determine the remaining space.
4. With the tire installed and fully inflated on your wheel, measure the widest of the rim or tire width to ensure that it fits.

WARNING

Contact between the tire or rim and the frame or fork may result in a loss of control while riding and potentially serious injury. Failure to follow these guidelines may result in damage to the frame not covered by Cervélo Limited Lifetime Warranty.

INTENDED USE OF THE R5-CX BICYCLE

WARNING

Understand your bike and its intended use. Choosing the wrong bicycle for your purpose can be hazardous. Using your bike the wrong way is dangerous.

No one type of bicycle is suited for all purposes. Your retailer can help you pick the "right tool for the job" and help you understand its limitations. There are many types of bicycles and many variations within each type. There are many types of mountain, road, racing, hybrid, touring, cyclocross and tandem bicycles. There are also bicycles that mix features. For example, there are road/racing bikes with triple cranks. These bikes have the low gearing of a touring bike, the quick handling of a racing bike, but are not well suited for carrying heavy loads on a tour. For that purpose you want a touring bike.

Within each of type of bicycle, one can optimize for certain purposes. Visit your bicycle shop and find someone with expertise in the area that interests you. Do your own homework. Seemingly small changes such as the choice of tires can improve or diminish the performance of a bicycle for a certain purpose.

NOTE: Usage conditions are generalized and evolving. Consult your retailer or Cervélo Customer Service about how you intend to use your bike.

NOTE: Cervélo bicycles are tested to a maximum combined bicycle/rider/luggage weight of 100kg. Components have different weight limits, and if replaced can alter the maximum safe bike weight limit. Consult your retailer or Cervélo Customer Service about what components are appropriate for your bicycle.

Maximum Weight Limit - Cervélo R5-CX

Rider	194 lbs	88 kg
Gear*	11 lbs	5 kg
Total	220.5 lbs	100 kg

*Seat bag / water bottles / bento bag / handlebar bottle / storage mounts only

Cyclocross Riding - Condition 2

Bikes designed for riding Condition 1, plus unpaved and gravel roads and trails with moderate grades. Contact with irregular terrain and loss of tire contact with the ground may occur. Drops should be no more than 6" (15cm).

Intended For cyclocross riding, training and racing. Cyclocross involves riding on a variety of terrain and surfaces including dirt or mud surfaces. Cyclocross bikes also work well for all weather rough road riding and commuting.

Not Intended For off road or mountain bike use, or jumping. Cyclocross riders and racers dismount before reaching an obstacle, carry their bike over the obstacle, and then remount. Cyclocross bikes are not intended for mountain bike use. The relatively large road bike size wheels are faster than smaller mountain bike wheels, but not as strong.

R5-CX TORQUE SPECIFICATIONS

Correct tightening torque of threaded fasteners is crucial to your safety. Always tighten fasteners to the correct torque. In case of a conflict between the instructions in this manual and those provided by a component manufacturer, consult with your retailer or with Cervélo Customer Service for clarification. Fasteners that are too tight can stretch and deform. Fasteners that are too loose can move and fatigue. Either mistake can lead to a sudden failure of the fastener.

Use only a correctly calibrated torque wrench to tighten critical fasteners on your bike. Carefully follow the torque wrench manufacturer's instructions on how to set and use the tool for accurate results. Ensure you read all relevant documentation and have the correct tools prior to attempting any adjustments yourself.

It is recommended that you permit your retailer to perform the following adjustments, as they have the proper tools and experience to ensure it is done correctly.

Prior to assembling and tightening any bolts, all threads must be generously greased with a quality, non-lithium type grease unless the bolt is pre-coated with Loctite® thread locker. All bolts should have either grease or Loctite - but never both. Torque wrenches with scale appropriate for the particular torque setting are strongly recommended for tightening all threaded fasteners.

Cervélo strongly recommends the use of carbon assembly compound/friction paste for all areas of clamping to carbon fiber, such as the seatpost

to frame, the stem to fork, and the handlebar to stem joints. Benefits to using this paste include reduced corrosion potential, and a decrease in required clamping force needed to support a given load. The paste should be evenly spread on the carbon surface under the clamped area, and the applicable bolt tightened as per the following recommendations.

WARNING: In case of a disagreement or a conflict between the following list and any supplier literature on recommended torque values for original equipment components, please contact Cervélo Customer Support for review and clarification of the required torque prior to installation.

Component	Torque (Nm)	Notes
Frame		
Bottom bracket- threaded -T47	50 Nm	Clean & grease the BB shell threads inside the frame. Grease the outside threads of the BB cups. Thread both sides of the BB cups into the frame- noting that the right side cup is reverse threaded. Using a torque wrench and the appropriate adaptor, tighten both sides to the specified torque until they are flush with the frame.
Rear derailleur fixing nut (disc brake)	12 to 15 Nm	Finger tight prior to rear wheel installation, final torque to approximate torque using open ended wrench.
Removable FDM / FDM blanking plate	3 Nm	Lightly grease the fixing screws.
Water bottle cage fixing screws	2 to 3 Nm	Lightly grease the fixing screws.

R5-CX TORQUE SPECIFICATIONS

Component	Torque (Nm)	Notes
Fork		
Fork steerer compression plug	8 Nm	Lightly grease the fixing screw and tighten to the recommended torque.
Fork dropout insert	3 Nm	Lightly grease screw, install finger tight on NDS fork dropout. Install the axle (no wheel), and tighten until the axle flange meets the fork dropout- then tighten the fixing screw to recommended torque. Remove the axle, install the axle & wheel to recommended torque, then remove. Re-torque the fixing screw to recommended torque
Stem		
Stem to fork steerer tube	5 Nm	Lightly coat the fork steerer at the stem clamping interface with carbon assembly compound. Tighten the stem fixing screws evenly & alternately to the recommended torque using a torque wrench.
Stem to carbon handlebar	6 Nm	Coat the stem/handlebar clamping surfaces with carbon assembly compound. Tighten the faceplate fixing screws in a star pattern to recommended maximum torque using a torque wrench.
Handlebar		
Brake/shift levers (to handlebar)	6 to 8 Nm	Refer to manufacturer's instructions for installation of brake/shift levers.
Accessory mount- front	2 Nm	Lightly grease the fixing screws.
Seatpost Clamp (frame to seatpost)		
D-shape collar	6 Nm	Use carbon assembly compound between the seatpost and the frame.
Secondary D-shape collar	3 Nm	
Saddle (seatpost head bolts) – SP24 D-shape carbon		
2 bolt head	8 to 9 Nm	Ensure Loctite 242 is used on both bolts (1 is pre-applied).
Wheels		
Cervélo aero thru-axle / Cervélo aero thru-axle with removable handle	12 to 15 Nm	Requires the use of a 6mm allen key type wrench or Removable handle.
Other		
Pedals	30 to 35 Nm	Refer to manufacturer's instructions.

R5-CX FRAME DETAILS

R5-CX (FM153)	
Bike Name	R5-CX
Model Year	2023
Serial Number Code	SN153
Frame Code	FM153
Fork Code	FK153
Brake Mount Type	Flat Mount Disc
Chainstay Height (Flat Mount)	25 mm
Frame Sizes	51/54/56/58
Wheel Size	700c
BB Type	T47 BBRight (T47A) Threaded
Headset Type	Integrated 1-1/4" x 1-1/2"


* Tire measurements shall be taken at the widest point of the tire when it is installed on the rim and inflated. 4 mm of distance is required between the tire and any frame or fork element.

NOTE: For UCI sanctioned cyclocross races, the maximum tire width is 33mm.

R5-CX (FM153)	
Upper Headset Bearing Dimensions	1-1/4", 34 x 46.8 x 7, 45° x 45°
Lower Headset Bearing Dimensions	1-1/2", 40 x 51.8 x 7.5, 36° x 45°
Seatpost	SP-SP24-ZERO, SP-SP24-15MM
Seatpost Clamp	SPC-256
Rear Derailleur Hanger	DRH-WMN112
Rear Derailleur Hanger (Shimano DM)	DRH-SDM
Front Derailleur Hanger	FDM-590
Front Thru-Axle Dimensions	12 x 100 mm
Rear Thru-Axle Dimensions	12 x 142 mm
Fork Dropout Insert	QRI-THD
Maximum Tire Width (Actual)	43 mm with 5 mm clearance*

R5-CX FRAME GEOMETRY

R5-CX (FM153)	51cm	54cm	56cm	58cm
Reach mm	371	380	389	398
Stack mm	520	540	560	580
Bottom Bracket Drop mm	63	63	63	63
Chainstay Length mm	425	425	425	425
Seat Tube Angle	74.5°	74°	73.5°	73°
Head Tube Angle	71.5°	71.5°	71.5°	72°
Fork Length (Axle to Crown) mm	401	401	401	401
Fork Offset mm	51	51	51	48
Front Center mm	581	597	612	620
Head Tube Length mm	97	118	139	157
Wheelbase mm	998	1014	1029	1037
Standover Height mm	775	789	803	820
Seat Tube Length mm	537	550	560	575
Top Tube Length mm	517	536	556	574



CERVÉLO CUSTOMER SUPPORT

Contacting Customer Support

Visit www.cervelo.com/contact-us to submit a question to Cervélo.

Product Registration

Visit www.cervelo.com/support to register your Cervélo bicycle through your MyCervélo account.

Manuals

Visit www.cervelo.com/product-manuals for additional information on Cervélo products.

Warranty

Visit www.cervelo.com/warranty for information on Cervélo's warranty policy.

ES

R5-CX RETAILER ASSEMBLY MANUAL

CER-CXA-V1 2022-05-25

www.cervelo.com

cerve